

Foveation Improves Payload Capacity in Steganography

Lifeng Qiu Lin
University College London
London, UK
lifeng.qiu.lin.lq@gmail.com

Henry Kam
New York University
New York, USA
henry.j.kam@gmail.com

Qi Sun
New York University
New York, USA
qisun0@gmail.com

Kaan Akşit
University College London
London, UK
kaanaksit@kaanaksit.com

Abstract

Steganography finds its use in visual medium such as providing metadata and watermarking. With support of efficient latent representations and foveated rendering, we trained models that improve existing capacity limits from 100 to 500 bits, while achieving better accuracy of up to 1 failure bit out of 2000, at 200K test bits. Finally, we achieve a comparable visual quality of 31.47 dB PSNR and 0.13 LPIPS, showing the effectiveness of novel perceptual design in creating multi-modal latent representations in steganography.

CCS Concepts

• **Computing methodologies** → **Image representations; Perception**; *Learning latent representations; Image processing; Reconstruction*; • **Computer systems organization** → *Redundancy*; • **Information systems** → *Multimedia content creation*.

ACM Reference Format:

Lifeng Qiu Lin, Henry Kam, Qi Sun, and Kaan Akşit. 2025. Foveation Improves Payload Capacity in Steganography. In *SIGGRAPH Asia 2025 Posters (SA Posters '25)*, December 15-18, 2025. ACM, New York, NY, USA, 2 pages. <https://doi.org/10.1145/3757374.3771423>

1 Introduction

Steganography concerns about hiding data in another medium [Wang et al. 2023]. More specifically, our work studies embedding information in images. Steganography is therefore useful in conveying multi-modal information such as labels, scene descriptions, or copyright marks. Growing number of AI-generated content and introduction of AR/VR systems increases its importance further by broadening the application scope [Rezaei et al. 2024].

Our work leverages latent representations [Yilmaz et al. 2024] and a foveated rendering loss [Walton et al. 2022] to increase payload capacity in steganography. With only 2000 training images, we achieve bit accuracy of 99.99% for 40K test set bits. Concerning state of the art in latent methods [Bui et al. 2023], our approach increases the payload capacity from 100 bits up to 500 bits with up to 100% recovery under non-distortion condition, 27.56 db PSNR and 0.26 LPIPS. Our final contribution is the introduction of Metameric Foveated Rendering loss in steganography, which noticeably improves all visual metrics and quality with respect to classic L2 loss.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

SA Posters '25, Hong Kong, Hong Kong

© 2025 Copyright held by the owner/author(s).

ACM ISBN 979-8-4007-2134-2/2025/12

<https://doi.org/10.1145/3757374.3771423>




Figure 1: Visual example of stego and payload recovery using our proposed foveated steganography and RoSteALS (Source: MetFaces [Karras et al. 2020]).

2 Method

Considering a message payload $P \in \{0, 1\}^k$ consisting of k bits and an input image (cover) $I \in \mathbb{R}^{h \times w \times c}$, find two functions H and R , to produce an output image (stego), $H(I, P) = I' \in \mathbb{R}^{h \times w \times c}$, and output payload, $R(I') = P' \in \{0, 1\}^k$. The aim is to reduce the distortion between I and I' while maximizing the accuracy between P and P' .




Figure 2: Our proposed foveated steganography approach (Source: MetFaces [Karras et al. 2020]).

Table 1: Table of results. Baseline is trained on MSE. RoSteALS uses MSE & LPIPS. Metameric solely relies on Metameric Loss.

Experiment	Resolution	Capacity	Bit Accuracy	MSE	PSNR	SSIM	LPIPS	Metameric Loss
Benchmark Baseline (RoSteALS)	256	100	0.9942	0.0009	32.16	0.8971	0.0780	0.0016
Vanilla Baseline	256	100	1	0.0015	28.90	0.8833	0.1621	0.0072
Vanilla Baseline	256	200	1	0.0018	28.37	0.8681	0.2047	0.0072
Metameric Baseline	256	200	0.9998	0.0010	31.47	0.8871	0.1288	0.0017
Vanilla Baseline	256	500	0.9997	0.0021	27.56	0.8348	0.2613	0.0077
—	—	—	—	—	—	—	—	—
Vanilla Baseline	128	500	0.4997	0.0007	33.11	0.9061	0.0570	0.0023

Our framework approaches this problem as depicted in Figure 2. In the hiding stage, a frozen image encoder, E , transforms input image into a latent representation, $E(I) = Z_i$. Payload embedder, F , creates also a learned representation, $P(I) = Z_p$. Together, they are manipulated by the merger, M , producing a merged latent, $M(Z_i, Z_p) = Z_m$, which a frozen image generator, G , uses to reconstruct the output image, $G(Z_m) = I'$. Finally, a payload retriever, R , extracts the output payload, $R(I') = P'$. The loss function is defined as the combination of payload and image quality losses, being BCE and Metameric Foveated Rendering [Walton et al. 2022] (defaulted to center) losses respectively. Formally, $\mathcal{L}_{total} = \mathcal{L}_{payload} + \lambda_i \cdot \mathcal{L}_{image} = \text{BCE}(P, P') + \lambda_i \cdot (\text{MetamericLoss}(I, I'))$, where λ_i controls the trade-off between the two losses.

The dataset is a balanced mixture of 2000 training, 400 validation, and 400 test images from MetFaces [Karras et al. 2020] and CLIC datasets [Toderici et al. 2020]. For preprocessing, images are randomly cropped and padded to the size of input and normalized as autoencoder requires. Notably, this dataset is much smaller than typical datasets used for the same purpose, but is found sufficient to learn performing 100-bits steganography, within controlled computing resources, about two hours on a single RTX 4090 GPU.

3 Results and Discussion

The frozen pair of image encoder and image generator to create a high-quality latent representation, is the F4-with-attention version autoencoder from LDM VQGAN series [Rombach et al. 2022]. After evaluating empirically, we found its high reconstruction quality is suitable for the embedding process. Compared to other backbones, this one converges slower at payload embedding, but achieves better image quality in the end. Keeping payload embedder as a fully connected layers is sufficient to encode the information after experimentation. For merger, the best performing architecture is adding two convolutional layer sandwiching the sum of image and payload latent, to soften the transition. Finally, ResNet50 was used as payload retriever as a popular and well-studied architecture.

Apart from common metrics, we also report Metameric Loss, which is a perceptual criterion akin to foveated gaze. Modeling the human visual system, this loss is more forgiving of visual distortions in the periphery and more harsh in the fovea.

The main results are shown in Table 1. Baselines achieved expanding payload capacities, at various resolutions. At minimal setting, baseline has a bit accuracy of 99.99%, failing to decode only 4 out of 40K test bits. Noticeably, we achieve 100% recovery in the native resolution of benchmark, RoSteALS [Bui et al. 2023], while

other settings also all exceed 99.95% compared to benchmark failing to reach 99.5%. Nevertheless, RoSteALS has better perceptual image quality. This is reasonable since it is an augmented version of the baseline which uses larger datasets, incorporates LPIPS in loss, and applies finer-grained optimization in the training.

Compared to baseline, Metameric Loss consistently improves the quality of the reconstructed images while keeping same level of bit accuracy. Compared to the benchmark, Figure 1 shows an example of resulting stego and recovered payload. This shows effectiveness of this visual technique in enhancing perceptual fidelity of images.

Despite successfully unlocking higher message length, we notice tangible limits of payload capacity, such as failing to learn 500-bit payload at 128 resolution. Resolution bounds the upper payload capacity under similar perceptual fidelity of images, and we hope to enhance this by introducing gaze as a new parameter. Future directions include exploring robustness under various distortions, subjective experiments to compare visual quality, and ablation studies with same capacity benchmarks. This work provides a light-weighted, human-centered, latent-based steganography framework which boosts payload capacity and accuracy while maintaining image quality. By satiating the need of large capacity in transmitting messages, we step towards practical applications of steganography in real-world scenarios.

References

- Tu Bui, Shruti Agarwal, Ning Yu, and John Collomosse. 2023. Rosteals: Robust steganography using autoencoder latent space. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*. 933–942.
- Tero Karras, Miika Aittala, Janne Hellsten, Samuli Laine, Jaakko Lehtinen, and Timo Aila. 2020. Training generative adversarial networks with limited data. *Advances in neural information processing systems* 33 (2020), 12104–12114.
- Ahmad Rezaei, Mohammad Akbari, Saeed Ranjbar Alvar, Arezou Fatemi, and Yong Zhang. 2024. Lawa: Using latent space for in-generation image watermarking. In *European Conference on Computer Vision*. Springer, 118–136.
- Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. 2022. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*. 10684–10695.
- George Toderici, Wenzhe Shi, Radu Timofte, Lucas Theis, Johannes Balle, Eirikur Agustsson, Nick Johnston, and Fabian Mentzer. 2024, 2022, 2021, 2020. Workshop and challenge on learned image compression (CLIC2020 to CLIC2024). In *CVPR*.
- David R Walton, Koray Kavakli, Rafael Kuffner Dos Anjos, David Swapp, Tim Weyrich, Hakan Urey, Anthony Steed, Tobias Ritschel, and Kaan Akşit. 2022. Metameric varifocal holograms. In *2022 IEEE Conference on Virtual Reality and 3D User Interfaces (VR)*. IEEE, 746–755.
- Zihan Wang, Olivia Byrnes, Hu Wang, Ruoxi Sun, Congbo Ma, Huaming Chen, Qi Wu, and Minhui Xue. 2023. Data hiding with deep learning: A survey unifying digital watermarking and steganography. *IEEE Transactions on Computational Social Systems* 10, 6 (2023), 2985–2999.
- Doğa Yılmaz, Towaki Takikawa, Duygu Ceylan, and Kaan Akşit. 2024. Learned Single-Pass Multitasking Perceptual Graphics for Immersive Displays. *arXiv preprint arXiv:2408.07836* (2024).